


3.25"



Caution
This bag contains
MOISTURE-SENSITIVE DEVICES

LEVEL

If blank, see adjacent bar code label

1. Calculated shelf life in sealed bag: 12 months at < 40°C and < 90% relative humidity (RH)
2. Peak package body temperature: _____ °C
If blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must be
 - a) Mounted within: _____ hours of factory conditions
If blank, see adjacent bar code label
 - ≤ 30°C/60% RH, or
 - b) Stored per J-STD-033
4. Devices require bake, before mounting, if:
 - a) Humidity Indicator Card reads > 10% for level 2a - 5a devices or > 60% for level 2 devices when read at 23 ± 5°C
 - b) 3a or 3b not met
5. If baking is required, refer to IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: _____
If blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

06736 / 91309 DescoIndustries.com

3.75"

Moisture Warning Symbol and message clearly shown on label.

Item	Description	Qty/Roll
06736	3.25" x 3.75", Permanent Adhesive	100

COLOR: White with blue printing

SYMBOL: JEDEC J-STD-033B

PACKAGED: 100 per roll, 3" diameter core

PRODUCT SPECIFICATIONS:

Adhesive: B-82, strong and permanent
 Liner: 40# white Kraft
 Facestock: 60# SemiGloss Litho
 Service Temperature: -10 to +180°F
 Minimum Labelling Temperature: +15°F

INK & VARNISH SPECIFICATIONS:

Water Resistance: Excellent
 Grease Resistance: Excellent
 Alcohol Resistance: Excellent
 UV Resistance: Excellent



LABEL, MOISTURE BARRIER BAG, IPC/JEDEC J-STD 020, ROLL 100

DESCO

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com, PHONE (909) 627-8178
DESCO EAST: 90 HUDSON RD, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER
06736

DATE:
May
2013